

LED Maschinenleuchte



LED machine light



TUBELED_70, 100°, 300 mm, 90-305V AC

Artikel-Nr.: 110310-11
EAN: 4260556621395

Bestell-Nr.: 110310-11
Modell: TUBELED_70 AC
Bauform: LED Aufbauleuchte für Maschinen
Leuchtmittel: SMD LED
Lampenleistung: ~17 W
Lampenlichtstrom: 1848 lm
Lampenlichtausbeute: ca. 132 lm/W
Lichtverteilung: direkt
Lichtfarbe: Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte: 90-305V AC \pm 10%, 50-60 Hz
Betriebsgerät: integriert
Anschluss Leuchte: M12 S-kodiert
Schutzart: IP67/IP69K
Schutzklasse: I
Entblendung: opalweiß
Abstrahlwinkel: 100°
Betriebstemperatur: -10... +50 °C
Farbwiedergabe (Ra): > 85
Lampenlebensdauer: > 50.000 h
Material Gehäuse: Aluminium
Material Abdeckung: Sicherheitsglas gefrostet, sprungsicher
Höhe [B] x Breite [C]: Ø 70 mm
Länge [A]: 300 mm
Gewicht: 1300 g
Bruttogewicht: 1700 g
Risikogruppe (DIN EN 62471): Gruppe 1
Kennzeichnung: CE, UKCA
Befestigungszubehör: optional
Gefertigt in: Deutschland
Besonderheit: Retrofitting: genormte LED Rohrleuchte zum 1:1 Austausch



Lampenlebensdauer in Betriebstunden (L80/B10)

LED Maschinenleuchte
LED machine light



TUBELED_70, 100°, 300 mm, 90-305V AC

Item number: 110310-11
EAN: 4260556621395

Order number: 110310-11
Model: TUBELED_70 AC
Type: LED surface-mounted luminaire for machines
Illuminant: SMD LED
Power consumption: ~17 W
Lamp luminous flux: 1848 lm
Lamp luminous efficiency: ca. 132 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)

Connected load: 90-305V AC \pm 10%, 50-60 Hz
Power supply: inbuilt
Connection (connector): M12 S-type encoded
Degree of protection: IP67/IP69K

Class of protection: I
Glare-free opal white

Beam angle (optics): 100°
Operating temperature: -10... +50 °C

Colour rendering (Ra): > 85
Lamps lifetime: > 50,000 h

Housing material: aluminium
Cover material: safety glass, frosted, shatterproof


Height [B] x Width [C]: Ø 70 mm
Length [A]: 300 mm

Weight (net): 1300 g
Gross weight: 1700 g


Risk group (DIN EN 62471): group 1
Marking: CE, UKCA

Mounting accessories: optional
Made in: Germany

Feature: retrofitting: standardised LED luminaire for 1:1 replacement



110310-11



Lamps lifetime in operation hours (L80/B10)