

LED Maschinenleuchte


LED machine light




TUBELED_70, 100°, 560 mm, 90-305V AC

Artikel-Nr.: 110410-12
EAN: 4260556621418

Bestell-Nr.: 110410-12
Modell: TUBELED_70 AC
Bauform: LED Aufbauleuchte für Maschinen
Leuchtmittel: SMD LED
Lampenleistung: ~28 W
Lampenlichtstrom: 3032 lm
Lampenlichtausbeute: ca. 132 lm/W
Lichtverteilung: direkt
Lichtfarbe: Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte: 90-305V AC \pm 10%, 50-60 Hz
Betriebsgerät: integriert
Anschluss Leuchte: M12 S-kodiert
Schutzart: IP67/IP69K
Schutzklasse: I
Entblendung: opalweiß
Abstrahlwinkel: 100°
Betriebstemperatur: -10... +50 °C
Farbwiedergabe (Ra): > 85
Lampenlebensdauer: > 50.000 h
Material Gehäuse: Aluminium
Material Abdeckung: Sicherheitsglas gefrostet, sprungsicher
Höhe [B] x Breite [C]: Ø 70 mm
Länge [A]: 560 mm
Gewicht: 2100 g
Bruttogewicht: 2550 g
Risikogruppe (DIN EN 62471): Gruppe 1
Kenzeichnung: CE, UKCA
Befestigungszubehör: optional
Gefertigt in: Deutschland
Besonderheit: Retrofitting: genormte LED Rohrleuchte zum 1:1 Austausch



110410-12



Lampenlebensdauer in Betriebsstunden (L80/B10)


LED Maschinenleuchte
LED machine light



TUBELED_70, 100°, 560 mm, 90-305V AC

Item number: 110410-12
EAN: 4260556621418

Order number:	110410-12
Model:	TUBELED_70 AC
Type:	LED surface-mounted luminaire for machines
Illuminant:	SMD LED
Power consumption:	~28 W
Lamp luminous flux:	3032 lm
Lamp luminous efficiency:	ca. 132 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	90-305V AC \pm 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	M12 S-type encoded
Degree of protection:	IP67/IP69K
Class of protection:	I
Glare-free	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +50 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 50,000 h
Housing material:	aluminium
Cover material:	Safety glass, frosted, shatterproof
Height [B] x Width [C]:	\varnothing 70 mm
Length [A]:	560 mm
Weight (net):	2100 g
Gross weight:	2550 g
Risk group (DIN EN 62471):	Group 1
Marking:	CE, UKCA
Mounting accessories:	optional
Made in:	Germany
Feature:	retrofitting: standardised LED luminaire for 1:1 replacement



110410-12



Lamps lifetime in operation hours (L80/B10)