

LED Maschinenleuchte


LED machine light



TUBELED_70, 60°, 560 mm, 24V DC

Artikel-Nr.: 110414-02
EAN: 4260556621340

Bestell-Nr.:	110414-02
Modell:	TUBELED_70 DC
Bauform:	LED Aufbauleuchte für Maschinen
Leuchtmittel:	High Power LED
Lampenleistung:	~ 27 W
Lampenlichtstrom:	3052 lm
Lampenlichtausbeute:	ca. 116 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC ± 10%
Anschluss Leuchte:	M12 A-kodiert
Schutzart:	IP67/IP69K
Schutzklasse:	III
Entblendung:	opalweiß
Abstrahlwinkel:	60°
Betriebstemperatur:	-30... +70 °C
Farbwiedergabe (Ra):	> 80
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Sicherheitsglas gefrostet, sprungsicher
Höhe [B] x Breite [C]:	Ø 70 mm
Länge [A]:	560 mm
Gewicht:	1650 g
Bruttogewicht:	2100 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Kennzeichnung:	CE, UKCA, ETL Listed (5003526)
Befestigungszubehör:	optional
Dimmbar:	optional über Zubehör
Gefertigt in:	Deutschland
Besonderheit:	Retrofitting: genormte LED Rohrleuchte zum 1:1 Austausch



Lampenlebensdauer in Betriebsstunden (L80/B10)


LED Maschinenleuchte
LED machine light



TUBELED_70, 60°, 560 mm, 24V DC

Item number: 110414-02
EAN: 4260556621340

Order number: 110414-02
Model: TUBELED_70 DC
Type: LED surface-mounted luminaire for machines
Illuminant: High Power LED
Power consumption: ~ 27 W
Lamp luminous flux: 3052 lm
Lamp luminous efficiency: ca. 116 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)
Connected load: 24V DC \pm 10%
Connection (connector): M12 A-type encoded
Degree of protection: IP67/IP69K
Class of protection: III
Glare-free opal white
Beam angle (optics): 60°
Operating temperature: -30... +70 °C
Colour rendering (Ra): > 80
Lamps lifetime: > 60,000 h
Housing material: aluminium
Cover material: Safety glass, frosted, shatterproof
Height [B] x Width [C]: \varnothing 70 mm
Length [A]: 560 mm
Weight (net): 1650 g
Gross weight: 2100 g
Risk group (DIN EN 62471): free group
Marking: CE, UKCA, ETL Listed (5003526)
Mounting accessories: optional
Dimmable: via optional accessory
Made in: Germany
Feature: retrofitting: standardised LED luminaire for 1:1 replacement



110414-02



Lamps lifetime in operation hours (L80/B10)