

LED Maschinenleuchte


LED machine light



TUBELED_70, 60°, 1100 mm, 24V DC

Artikel-Nr.: 110514-02
EAN: 4260556621364

| | |
|-------------------------------------|--|
| Bestell-Nr.: | 110514-02 |
| Modell: | TUBELED_70 DC |
| Bauform: | LED Aufbauleuchte für Maschinen |
| Leuchtmittel: | High Power LED |
| Lampenleistung: | ~60 W |
| Lampenlichtstrom: | 6104 lm |
| Lampenlichtausbeute: | ca. 116 lm/W |
| Lichtverteilung: | direkt |
| Lichtfarbe: | Tageslichtweiß (5200 - 5700K) |
| Anschlusswert Leuchte: | 24V DC \pm 10% |
| Anschluss Leuchte: | M12 A-kodiert |
| Schutzart: | IP67/IP69K |
| Schutzklasse: | III |
| Entblendung: | opalweiß |
| Abstrahlwinkel: | 60° |
| Betriebstemperatur: | -30... +70 °C |
| Farbwiedergabe (Ra): | > 80 |
| Lampenlebensdauer: | > 60.000 h |
| Material Gehäuse: | Aluminium |
| Material Abdeckung: | Sicherheitsglas gefrostet, sprungsicher |
| Höhe [B] x Breite [C]: | \varnothing 70 mm |
| Länge [A]: | 1100 mm |
| Gewicht: | 2950 g |
| Bruttogewicht: | 3750 g |
| Risikogruppe (DIN EN 62471): | freie Gruppe |
| Kennzeichnung: | CE, UKCA, ETL Listed (5003526) |
| Befestigungszubehör: | optional |
| Dimmbar: | optional über Zubehör |
| Gefertigt in: | Deutschland |
| Besonderheit: | Retrofitting: genormte LED Rohrleuchte zum 1:1 Austausch |



Lampenlebensdauer in Betriebstunden (L80/B10)



LED Maschinenleuchte
LED machine light



TUBELED_70, 60°, 1100 mm, 24V DC

Item number: 110514-02
EAN: 4260556621364

| | |
|-----------------------------------|--|
| Order number: | 110514-02 |
| Model: | TUBELED_70 DC |
| Type: | LED surface-mounted luminaire for machines |
| Illuminant: | High Power LED |
| Power consumption: | ~60 W |
| Lamp luminous flux: | 6104 lm |
| Lamp luminous efficiency: | ca. 116 lm/W |
| Light distribution: | direct |
| Light colour: | daylight white (5200 - 5700K) |
| Connected load: | 24V DC \pm 10% |
| Connection (connector): | M12 A-type encoded |
| Degree of protection: | IP67/IP69K |
| Class of protection: | III |
| Glare-free | opal white |
| Beam angle (optics): | 60° |
| Operating temperature: | -30... +70 °C |
| Colour rendering (Ra): | > 80 |
| Lamps lifetime: | > 60,000 h |
| Housing material: | aluminium |
| Cover material: | Safety glass, frosted, shatterproof |
| Height [B] x Width [C]: | \varnothing 70 mm |
| Length [A]: | 1100 mm |
| Weight (net): | 2950 g |
| Gross weight: | 3750 g |
| Risk group (DIN EN 62471): | free group |
| Marking: | CE, UKCA, ETL Listed (5003526) |
| Mounting accessories: | optional |
| Dimmable: | via optional accessory |
| Made in: | Germany |
| Feature: | retrofitting: standardised LED luminaire for 1:1 replacement |



Lamps lifetime in operation hours (L80/B10)