

## LED Maschinenleuchte



### LED machine light



## MIDILED LED Aufbauleuchte

**Artikel-Nr.:** 110614-01  
**EAN:** 4260556620886

<b>Bestell-Nr.:</b>	110614-01
<b>Modell:</b>	MIDILED
<b>Bauform:</b>	LED Aufbauleuchte
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~7 W
<b>Lampenlichtstrom:</b>	882 lm
<b>Lampenlichtausbeute:</b>	122 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24 V DC
<b>Betriebsgerät:</b>	-
<b>Anschluss Leuchte:</b>	M12 A-kodiert
<b>Schutzart:</b>	IP68
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	ESG matt, sprungsicher
<b>Abstrahlwinkel:</b>	120°
<b>Betriebstemperatur:</b>	-10... +40 °C
<b>Farbwiedergabe (Ra):</b>	> 80
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	Sicherheitsglas gefrostet
<b>Länge [A]:</b>	ca. 148 mm
<b>Gewicht:</b>	400 g
<b>Bruttogewicht:</b>	550 g
<b>Risikogruppe (DIN EN 62471):</b>	freie Gruppe
<b>Befestigungszubehör:</b>	Haltewinkel inklusive
<b>Dimmbar:</b>	optional über Zubehör
<b>Kennzeichnung:</b>	CE, UKCA
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	kompakt, sehr lichtstark



Lampenlebensdauer in Betriebsstunden (L80/B10)



LED Maschinenleuchte  
LED machine light



MIDILED LED surface mounted luminaire

**Item number:** 110614-01  
**EAN:** 4260556620886

<b>Order number:</b>	110614-01
<b>Model:</b>	MIDILED
<b>Type:</b>	LED surface-mounted luminaire
<b>Illuminant:</b>	SMD LED
<b>Power consumption:</b>	~7 W
<b>Lamp luminous flux:</b>	822 lm
<b>Lamp luminous efficiency:</b>	122 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	daylight white (5200 - 5700K)
<b>Connected load:</b>	24 V DC
<b>Power supply:</b>	-
<b>Connection (connector):</b>	M12 A-type encoded
<b>Degree of protection:</b>	IP68
<b>Class of protection:</b>	III
<b>Glare-free</b>	ESG frosted, shatterproof
<b>Beam angle (optics):</b>	120°
<b>Operating temperature:</b>	-10... +40 °C
<b>Colour rendering (Ra):</b>	> 80
<b>Lamps lifetime:</b>	> 60,000 h
<b>Housing material:</b>	aluminium
<b>Cover material:</b>	safety glass frosted
<b>Length [A]:</b>	ca. 148 mm
<b>Weight (net):</b>	400 g
<b>Gross weight:</b>	550 g
<b>Risk group (DIN EN 62471):</b>	free group
<b>Mounting accessories:</b>	holding angle in delivery scope
<b>Dimmable:</b>	via optional accessory
<b>Marking:</b>	CE, UKCA
<b>Made in:</b>	Germany
<b>Feature:</b>	compactly built, very bright



Lamps lifetime in operation hours (L80/B10)