

LED Maschinenleuchte


LED machine light



TUBELED_70, 60°, 1580 mm, 90-305V AC

Artikel-Nr.: 110714-12
EAN: 4260556621463

Bestell-Nr.:	110714-12
Modell:	TUBELED_70 AC
Bauform:	LED Aufbauleuchte für Maschinen
Leuchtmittel:	High Power LED
Lampenleistung:	~85 W
Lampenlichtstrom:	9156 lm
Lampenlichtausbeute:	ca. 116 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	90-305V AC ± 10%, 50-60 Hz
Betriebsgerät:	integriert
Anschluss Leuchte:	M12 S-kodiert
Schutzart:	IP67/IP69K
Schutzklasse:	I
Entblendung:	opalweiß
Abstrahlwinkel:	60°
Betriebstemperatur:	-10... +50 °C
Farbwiedergabe (Ra):	> 80
Lampenlebensdauer:	> 50.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Sicherheitsglas gefrostet, sprungsicher
Höhe [B] x Breite [C]:	Ø 70 mm
Länge [A]:	1580 mm
Gewicht:	4750 g
Bruttogewicht:	5950 g
Risikogruppe (DIN EN 62471):	Gruppe 1
Kenzeichnung:	CE, UKCA
Befestigungszubehör:	optional
Gefertigt in:	Deutschland
Besonderheit:	Retrofitting: genormte LED Rohrleuchte zum 1:1 Austausch



Lampenlebensdauer in Betriebsstunden (L80/B10)


LED Maschinenleuchte
LED machine light



TUBELED_70, 60°, 1580 mm, 90-305V AC

Item number: 110714-12
EAN: 4260556621463

Order number: 110714-12
Model: TUBELED_70 AC
Type: LED surface-mounted luminaire for machines
Illuminant: High Power LED
Power consumption: ~85 W
Lamp luminous flux: 9156 lm
Lamp luminous efficiency: ca. 116 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)
Connected load: 90-305V AC \pm 10%, 50-60 Hz
Power supply: inbuilt
Connection (connector): M12 S-type encoded
Degree of protection: IP67/IP69K
Class of protection: I
Glare-free opal white
Beam angle (optics): 60°
Operating temperature: -10... +50 °C
Colour rendering (Ra): > 80
Lamps lifetime: > 50,000 h
Housing material: aluminium
Cover material: safety glass, frosted, shatterproof
Height [B] x Width [C]: Ø 70 mm
Length [A]: 1580 mm
Weight (net): 4750 g
Gross weight: 5950 g
Risk group (DIN EN 62471): group 1
Marking: CE, UKCA
Mounting accessories: optional
Made in: Germany
Feature: retrofitting: standardised LED luminaire for 1:1 replacement



Lamps lifetime in operation hours (L80/B10)