

LED Arbeitsplatzleuchte



LED workplace light



UNILED SL, 295 mm, 24V DC, Abdeckung Opalweiß

Artikelnr.: 110914-11
EAN: 4260556620312

Bestell-Nr.:	110914-11
Modell:	UNILED SL
Bauform:	LED System- und Arbeitsplatzleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~15 W
Lampenlichtstrom:	1617 lm
Lampenlichtausbeute:	131 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC \pm 10%
Anschluss Leuchte:	M12 A-kodiert
Schutzart:	IP50
Schutzklasse:	III
Entblendung:	opalweiß
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +60 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Kunststoff matt
Höhe [B] x Breite [C]:	35 mm x 85 mm
Länge [A]:	295 mm / 325 mm
Gewicht:	500 g
Bruttogewicht:	850 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Befestigungszubehör:	optional
Dimmbar:	optional über Zubehör
Kennzeichnung:	CE, UKCA, ETL Listed (5003529)
Gefertigt in:	Deutschland
Besonderheit:	Ausleuchtung homogen, schatten- und blendfrei



Lampenlebensdauer in Betriebsstunden (L80/B10)



LED Arbeitsplatzleuchte
LED workplace light



UNILED SL, 295 mm, 24V DC, opal white cover

Item number: 110914-11
EAN: 4260556620312

Order number: 110914-11
Model: UNILED SL
Type: LED system light and workplace lighting
Illuminant: SMD LED
Power consumption: ~15 W
Lamp luminous flux: 1617 lm
Lamp luminous efficiency: 131 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)
Connected load: 24V DC \pm 10%
Connection (connector): M12 A-type encoded
Degree of protection: IP50
Class of protection: III
Glare-free opal white
Beam angle (optics): 100°
Operating temperature: -10... +60 °C
Colour rendering (Ra): > 85
Lamps lifetime: > 60,000 h
Housing material: aluminium
Cover material: plastic soft
Height [B] x Width [C]: 35 mm x 85 mm
Length [A]: 295 mm / 325 mm
Weight (net): 500 g
Gross weight: 850 g
Risk group (DIN EN 62471): free group
Mounting accessories: optional
Dimmable: via optional accessory
Marking: CE, UKCA, ETL Listed (5003529)
Made in: Germany
Feature: homogeneous lighting, shadow- and glare-free



Lamps lifetime in operation hours (L80/B10)