

## LED Arbeitsplatzleuchte



### LED workplace light



## UNILED SL, 545 mm, 24V DC, Abdeckung Opalweiß

**Artikelnr.:** 110914-12  
**EAN:** 4260556620329

<b>Bestell-Nr.:</b>	110914-12
<b>Modell:</b>	UNILED SL
<b>Bauform:</b>	LED System- und Arbeitsplatzleuchte
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~24 W
<b>Lampenlichtstrom:</b>	3217 lm
<b>Lampenlichtausbeute:</b>	131 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC $\pm$ 10%
<b>Anschluss Leuchte:</b>	M12 A-kodiert
<b>Schutzart:</b>	IP50
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	opalweiß
<b>Abstrahlwinkel:</b>	100°
<b>Betriebstemperatur:</b>	-10... +60 °C
<b>Farbwiedergabe (Ra):</b>	> 85
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	Kunststoff matt
<b>Höhe [B] x Breite [C]:</b>	35 mm x 85 mm
<b>Länge [A]:</b>	545 mm / 575 mm
<b>Gewicht:</b>	850 g
<b>Bruttogewicht:</b>	1300 g
<b>Risikogruppe (DIN EN 62471):</b>	freie Gruppe
<b>Befestigungszubehör:</b>	optional
<b>Dimmbar:</b>	optional über Zubehör
<b>Kennzeichnung:</b>	CE, UKCA, ETL Listed (5003529)
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	Ausleuchtung homogen, schatten- und blendfrei



Lampenlebensdauer in Betriebsstunden (L80/B10)



LED Arbeitsplatzleuchte  
LED workplace light



UNILED SL, 545 mm, 24V DC, opal white cover

**Item number:** 110914-12  
**EAN:** 4260556620329

**Order number:** 110914-12  
**Model:** UNILED SL  
**Type:** LED system light and workplace lighting  
**Illuminant:** SMD LED  
**Power consumption:** ~24 W  
**Lamp luminous flux:** 3217 lm  
**Lamp luminous efficiency:** 131 lm/W  
**Light distribution:** direct  
**Light colour:** daylight white (5200 - 5700K)  
**Connected load:** 24V DC  $\pm$  10%  
**Connection (connector):** M12 A-type encoded  
**Degree of protection:** IP50  
**Class of protection:** III  
**Glare-free** opal white  
**Beam angle (optics):** 100°  
**Operating temperature:** -10... +60 °C  
**Colour rendering (Ra):** > 85  
**Lamps lifetime:** > 60,000 h  
**Housing material:** aluminium  
**Cover material:** plastic soft  
**Height [B] x Width [C]:** 35 mm x 85 mm  
**Length [A]:** 545 mm / 575 mm  
**Weight (net):** 850 g  
**Gross weight:** 1300 g  
**Risk group (DIN EN 62471):** free group  
**Mounting accessories:** optional  
**Dimmable:** via optional accessory  
**Marking:** CE, UKCA, ETL Listed (5003529)  
**Made in:** Germany  
**Feature:** homogeneous lighting, shadow- and glare-free



Lamps lifetime in operation hours (L80/B10)