

LED Arbeitsplatzleuchte



LED workplace light



UNILED SL, 1545 mm, 24V DC, Abdeckung Opalweiß

Artikel-Nr.: 110914-14
EAN: 4260556620343

Bestell-Nr.:	110914-14
Modell:	UNILED SL
Bauform:	LED System- und Arbeitsplatzleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~72 W
Lampenlichtstrom:	9634 lm
Lampenlichtausbeute:	131 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC \pm 10%
Anschluss Leuchte:	M12 A-kodiert
Schutzart:	IP50
Schutzklasse:	III
Entblendung:	opalweiß
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +60 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Kunststoff matt
Höhe [B] x Breite [C]:	35 mm x 85 mm
Länge [A]:	1545 mm / 1575 mm
Gewicht:	2400 g
Bruttogewicht:	3600 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Befestigungszubehör:	optional
Dimmbar:	optional über Zubehör
Kennzeichnung:	CE, UKCA, ETL Listed (5003529)
Gefertigt in:	Deutschland
Besonderheit:	Ausleuchtung homogen, schatten- und blendfrei



Lampenlebensdauer in Betriebsstunden (L80/B10)

LED Arbeitsplatzleuchte
LED workplace light



UNILED SL, 1545 mm, 24V DC,
opal white cover

Item number: 110914-14
EAN: 4260556620343

Order number: 110914-14
Model: UNILED SL
Type: LED system light and workplace lighting
Illuminant: SMD LED
Power consumption: ~72 W
Lamp luminous flux: 9634 lm
Lamp luminous efficiency: 131 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)

Connected load: 24V DC \pm 10%
Connection (connector): M12 A-type encoded
Degree of protection: IP50

Class of protection: III
Glare-free opal white

Beam angle (optics): 100°
Operating temperature: -10... +60 °C

Colour rendering (Ra): > 85
Lamps lifetime: > 60,000 h

Housing material: aluminium
Cover material: plastic soft



Height [B] x Width [C]: 35 mm x 85 mm
Length [A]: 1545 mm / 1575 mm

Weight (net): 2400 g
Gross weight: 3600 g

Risk group (DIN EN 62471): free group
Mounting accessories: optional

Dimmable: via optional accessory
Marking: CE, UKCA, ETL Listed (5003529)

Made in: Germany
Feature: homogeneous lighting, shadow- and glare-free



Lamps lifetime in operation hours (L80/B10)