

# LED Arbeitsplatzleuchte




## LED workplace light



### UNILED SL AC, 295 mm, 220-240V AC, Abdeckung Mikroprismen

**Artikel-Nr.:** 110914-61  
**EAN:** 4260556623535

<b>Bestell-Nr.:</b>	110914-61
<b>Modell:</b>	UNILED SL
<b>Bauform:</b>	LED System- und Arbeitsplatzleuchte
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~8,5 W
<b>Lampenlichtstrom:</b>	1030 lm
<b>Lampenlichtausbeute:</b>	127 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	220-240V AC ± 10%, 50-60 Hz
<b>Betriebsgerät:</b>	integriert
<b>Anschluss Leuchte:</b>	Anschlussleitung mit Netzstecker
<b>Schutzart:</b>	IP50
<b>Schutzklasse:</b>	I
<b>Entblendung:</b>	Mikroprismen
<b>Abstrahlwinkel:</b>	100°
<b>Betriebstemperatur:</b>	-10... +60 °C
<b>Farbwiedergabe (Ra):</b>	> 80
<b>Lampenlebensdauer:</b>	> 50.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	Kunststoff Mikroprismen
<b>Höhe [B] x Breite [C]:</b>	35 mm x 85 mm
<b>Länge [A]:</b>	295 mm / 325 mm
<b>Gewicht:</b>	600 g
<b>Bruttogewicht:</b>	950 g
<b>Risikogruppe (DIN EN 62471):</b>	Gruppe 1
<b>Befestigungszubehör:</b>	optional
<b>Kennzeichnung:</b>	CE, UKCA
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	Hohe Lichtstreuung, universell einsetzbar



Lampenlebensdauer in Betriebsstunden (L80/B10)

## LED Arbeitsplatzleuchte LED workplace light



### UNILED SL AC, 295 mm, 220-240V AC, micro prisms cover

**Item number:** 110914-61  
**EAN:** 4260556623535

**Order number:** 110914-61  
**Model:** UNILED SL  
**Type:** LED system light and workplace lighting  
**Illuminant:** SMD LED  
**Power consumption:** ~8,5 W  
**Lamp luminous flux:** 1030 lm  
**Lamp luminous efficiency:** 127 lm/W  
**Light distribution:** direct  
**Light colour:** daylight white (5200 - 5700K)  
**Connected load:** 220-240V AC ± 10%, 50-60 Hz  
**Power supply:** inbuilt

**Connection (connector):** connection cable with power plug  
**Degree of protection:** IP50

**Class of protection:** I  
**Glare-free** micro prisms

**Beam angle (optics):** 100°  
**Operating temperature:** -10... +60 °C

**Colour rendering (Ra):** > 80  
**Lamps lifetime:** > 50,000 h

**Housing material:** aluminium  
**Cover material:** micro prisms cover




**Height [B] x Width [C]:** 35 mm x 85 mm  
**Length [A]:** 295 mm / 325 mm

**Weight (net):** 600 g  
**Gross weight:** 950 g

**Risk group (DIN EN 62471):** group 1  
**Mounting accessories:** optional

**Marking:** CE, UKCA  
**Made in:** Germany

**Feature:** high light diffusion, universally applicable



Lamps lifetime in operation hours (L80/B10)