

LED Arbeitsplatzleuchte


LED workplace light



UNILED SL AC, 1070 mm, 220-240V AC, Zugpendel



Artikel-Nr.: 110914-83
EAN: 4260556623580

Bestell-Nr.:	110914-83
Modell:	UNILED SL
Bauform:	LED System- und Arbeitsplatzleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~34 W
Lampenlichtstrom:	5120 lm
Lampenlichtausbeute:	127 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	220-240V AC ± 10%, 50-60 Hz
Betriebsgerät:	integriert
Anschluss Leuchte:	1 Paar Zugpendel, Deckenübergabepunkt, 2 offene Kabelenden
Schutzart:	IP50
Schutzklasse:	I
Entblendung:	Mikroprismen
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +60 °C
Farbwiedergabe (Ra):	> 80
Lampenlebensdauer:	> 50.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Kunststoff Mikroprismen
Höhe [B] x Breite [C]:	35 mm x 85 mm
Länge [A]:	1070 mm
Zugpendel Auszugsbereich:	~740 mm - 1900 mm
Gewicht:	1900 g
Bruttogewicht:	2750 g
Risikogruppe (DIN EN 62471):	Gruppe 1
Kennzeichnung:	CE, UKCA
Gefertigt in:	Deutschland
Besonderheit:	Lichtintensität über Zugpendel einstellbar



Abstand d=100 cm

$E_{\text{mittel}} = 943 \text{ lux}$
 $E_{\text{max}} = 1224 \text{ lux}$
 $E_{\text{min}} = 578 \text{ lux}$



Lampenlebensdauer in Betriebsstunden (L80/B10)

LED Arbeitsplatzleuchte LED workplace light



UNILED SL AC, 1070 mm, 220-240V AC, adjustable pull pendants

Item number: 110914-83
EAN: 4260556623580

Order number: 110914-83

Model: UNILED SL

Type: LED system light and workplace lighting

Illuminant: SMD LED

Power consumption: ~34 W

Lamp luminous flux: 5120 lm

Lamp luminous efficiency: 127 lm/W

Light distribution: direct

Light colour: daylight white (5200 - 5700K)

Connected load: 220-240V AC \pm 10%, 50-60 Hz

Power supply: inbuilt

Connection (connector): 1 pair of adjustable pull pendants, ceiling transfer point via two open cable ends

Degree of protection: IP50

Class of protection: I

Glare-free micro prisms

Beam angle (optics): 100°

Operating temperature: -10... +60 °C

Colour rendering (Ra): > 80

Lamps lifetime: > 50,000 h

Housing material: aluminium

Cover material: micro prisms cover

Height [B] x Width [C]: 35 mm x 85 mm

Length [A]: 1070 mm

Pullout area of adjustable pendants: ~740 mm - 1900 mm

Weight (net): 1900 g


Gross weight: 2750 g

Risk group (DIN EN 62471): group 1



Marking: CE, UKCA

Made in: Germany

Feature: light intensity variable via adjustable pull pendants



Abstand d=100 cm
 $E_{\text{mittel}} = 943 \text{ lux}$
 $E_{\text{max}} = 1224 \text{ lux}$
 $E_{\text{min}} = 578 \text{ lux}$



Lamps lifetime in operation hours (L80/B10)