

LED Maschinenleuchte



LED machine light



LEANLED II, 1020 mm, klare Abdeckung

Artikel-Nr.: 111010-06
EAN: 4260556624051

Bestell-Nr.:	111010-06
Modell:	LEANLED II
Bauform:	LED Aufbauleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~24 W
Lampenlichtstrom:	3780 lm
Lampenlichtausbeute:	145 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC ± 10%
Anschluss Leuchte:	M12 A-kodiert
Schutzart:	IP54
Schutzklasse:	III
Abstrahlwinkel:	120°
Betriebstemperatur:	-10... +60 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Polycarbonat, klar, splitterfrei
Höhe [B] x Breite [C]:	31 mm x 26 mm
Länge [A]:	1020 mm
Gewicht:	700 g
Bruttogewicht:	1000 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Kennzeichnung:	CE, UKCA, ETL Listed (5003526)
Befestigungszubehör:	2 Paar Halterungen (drehbare oder planare Befestigung) im Lieferumfang
Dimmbar:	optional über Zubehör
Gefertigt in:	Deutschland



Lampenlebensdauer in Betriebsstunden (L80/B10)



LED Maschinenleuchte
LED machine light



LEANLED II, 1020 mm, clear cover

Item number: 111010-06
EAN: 4260556624051

Order number: 111010-06
Model: LEANLED II
Type: LED surface-mounted luminaire
Illuminant: SMD LED
Power consumption: ~24 W
Lamp luminous flux: 3780 lm
Lamp luminous efficiency: 145 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)
Connected load: 24V DC ± 10%
Connection (connector): M12 A-type encoded
Degree of protection: IP54
Class of protection: III
Beam angle (optics): 120°
Operating temperature: -10... +60 °C
Colour rendering (Ra): > 85
Lamps lifetime: > 60,000 h
Housing material: aluminium
Cover material: Polycarbonat, clear, shatterproof
Height [B] x Width [C]: 31 mm x 26 mm
Length [A]: 1020 mm
Weight (net): 700 g
Gross weight: 1000 g
Risk group (DIN EN 62471): free group
Marking: CE, UKCA, ETL Listed (5003526)
Mounting accessories: 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope
Dimmable: via optional accessory
Made in: Germany



Lamps lifetime in operation hours (L80/B10)