

LED Maschinenleuchte

LED machine light





LEANLED II, 180 mm, klare Abdeckung, kaskadierbar

Artikel-Nr.: 111010-21
EAN: 4260556624143

Bestell-Nr.: 111010-21
Modell: LEANLED II
Bauform: LED Aufbauleuchte
Leuchtmittel: SMD LED
Lampenleistung: ~4 W
Lampenlichtstrom: 630 lm
Lampenlichtausbeute: 145 lm/W
Lichtverteilung: direkt
Lichtfarbe: Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte: 24V DC ± 10%
Anschluss Leuchte: M12 A-kodiert
Schutzart: IP54

Schutzklasse: III
Abstrahlwinkel: 120°
Betriebstemperatur: -10... +60 °C
Farbwiedergabe (Ra): > 85
Lampenlebensdauer: > 60.000 h
Material Gehäuse: Aluminium
Material Abdeckung: Polycarbonat, klar, splitterfrei
Höhe [B] x Breite [C]: 31 mm x 26 mm
Länge [A]: 180 mm
Gewicht: 180 g
Bruttogewicht: 330 g
Risikogruppe (DIN EN 62471): freie Gruppe
Kennzeichnung: CE, UKCA, ETL Listed (5003526)
Befestigungszubehör: 2 Paar Halterungen (drehbare oder planare Befestigung) im Lieferumfang
Dimmbar: optional über Zubehör
Gefertigt in: Deutschland
Besonderheit: kaskadierbar, mehrere Leuchten lassen sich bis zu einer Gesamtstromstärke von max. 4A elektrisch verketteten



Lampenlebensdauer in Betriebsstunden (L80/B10)

LED Maschinenleuchte
LED machine light





LEANLED II, 180 mm, clear cover,
cascadable

Item number: 111010-21
EAN: 4260556624143

Order number: 111010-21
Model: LEANLED II
Type: LED surface-mounted luminaire
Illuminant: SMD LED
Power consumption: ~4 W
Lamp luminous flux: 630 lm
Lamp luminous efficiency: 145 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)
Connected load: 24V DC ± 10%
Connection (connector): M12 A-type encoded
Degree of protection: IP54

Class of protection: III
Beam angle (optics): 120°
Operating temperature: -10... +60 °C
Colour rendering (Ra): > 85
Lamps lifetime: > 60,000 h
Housing material: aluminium
Cover material: polycarbonat, clear, shatterproof
Height [B] x Width [C]: 31 mm x 26 mm
Length [A]: 180 mm
Weight (net): 180 g
Gross weight: 330 g

Risk group (DIN EN 62471): free group
Marking: CE, UKCA, ETL Listed (5003526)
Mounting accessories: 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope
Dimmable: via optional accessory
Made in: Germany
Feature: cascadable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.



Lamps lifetime in operation hours (L80/B10)