

# LED Maschinenleuchte

## LED machine light





## LEANLED II, 1520 mm, klare Abdeckung, kaskadierbar

**Artikel-Nr.:** 111010-27  
**EAN:** 4260556624204

**Bestell-Nr.:** 111010-27  
**Modell:** LEANLED II  
**Bauform:** LED Aufbauleuchte  
**Leuchtmittel:** SMD LED  
**Lampenleistung:** ~37 W  
**Lampenlichtstrom:** 5670 lm  
**Lampenlichtausbeute:** 145 lm/W  
**Lichtverteilung:** direkt  
**Lichtfarbe:** Tageslichtweiß (5200 - 5700K)

**Anschlusswert Leuchte:** 24V DC  $\pm$  10%  
**Anschluss Leuchte:** M12 A-kodiert  
**Schutzart:** IP54  
**Schutzklasse:** III  
**Abstrahlwinkel:** 120°  
**Betriebstemperatur:** -10... +60 °C  
**Farbwiedergabe (Ra):** > 85  
**Lampenlebensdauer:** > 60.000 h  
**Material Gehäuse:** Aluminium, Kunststoff  
**Material Abdeckung:** Polycarbonat, klar, splitterfrei  
**Höhe [B] x Breite [C]:** 31 mm x 26 mm  
**Länge [A]:** 1520 mm  
**Gewicht:** 950 g  
**Bruttogewicht:** 1450 g  
**Risikogruppe (DIN EN 62471):** freie Gruppe  
**Kennzeichnung:** CE, UKCA, ETL Listed (5003526)  
**Befestigungszubehör:** 2 Paar Halterungen (drehbare oder planare Befestigung) im Lieferumfang  
**Dimmbar:** optional über Zubehör  
**Gefertigt in:** Deutschland  
**Besonderheit:** kaskadierbar, mehrere Leuchten lassen sich bis zu einer Gesamtstromstärke von max. 4A elektrisch verketteten



Lampenlebensdauer in Betriebsstunden (L80/B10)

LED Maschinenleuchte  
LED machine light



LEANLED II, 1520 mm, clear cover,  
cascadable

**Item number:** 111010-27  
**EAN:** 4260556624204

**Order number:** 111010-27  
**Model:** LEANLED II  
**Type:** LED surface-mounted luminaire  
**Illuminant:** SMD LED  
**Power consumption:** ~37 W  
**Lamp luminous flux:** 5670 lm  
**Lamp luminous efficiency:** 145 lm/W

**Light distribution:** direct  
**Light colour:** daylight white (5200 - 5700K)  
**Connected load:** 24V DC  $\pm$  10%  
**Connection (connector):** M12 A-type encoded  
**Degree of protection:** IP54

**Class of protection:** III  
**Beam angle (optics):** 120°  
**Operating temperature:** -10... +60 °C

**Colour rendering (Ra):** > 85  
**Lamps lifetime:** > 60,000 h

**Housing material:** aluminium, plastics  
**Cover material:** polycarbonat, clear, shatterproof

**Height [B] x Width [C]:** 31 mm x 26 mm  
**Length [A]:** 1520 mm

**Weight (net):** 950 g  
**Gross weight:** 1450 g



**Risk group (DIN EN 62471):** free group  
**Marking:** CE, UKCA, ETL Listed (5003526)

**Mounting accessories:** 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope

**Dimmable:** via optional accessory

**Made in:** Germany

**Feature:** cascadable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.



Lamps lifetime in operation hours (L80/B10)