

LED Maschinenleuchte



LED machine light



LEANLED II, 180 mm, opalweiÙe Abdeckung, kaskadierbar

Artikel-Nr.: 111010-31
EAN: 4260556624211

Bestell-Nr.:	111010-31
Modell:	LEANLED II
Bauform:	LED Aufbauleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~4 W
Lampenlichtstrom:	630 lm
Lampenlichtausbeute:	145 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	TageslichtweiÙ (5200 - 5700K)
Anschlusswert Leuchte:	24V DC \pm 10%
Anschluss Leuchte:	M12 A-kodiert
Schutzart:	IP54
Schutzklasse:	III
Entblendung:	opalweiÙ
Abstrahlwinkel:	120°
Betriebstemperatur:	-10... +60 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material GehäÙe:	Aluminium
Material Abdeckung:	Polycarbonat, matt
HöÙe [B] x Breite [C]:	31 mm x 26 mm
Länge [A]:	180 mm
Gewicht:	180 g
Bruttogewicht:	330 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Kennzeichnung:	CE, UKCA, ETL Listed (5003526)
BefestigungszubehöÙr:	2 Paar Halterungen (drehbare oder planare Befestigung) im Lieferumfang
Dimmbar:	optional über ZubehöÙ
Gefertigt in:	Deutschland
Besonderheit:	kaskadierbar, mehrere Leuchten lassen sich bis max. 4A elektrisch verketteten



Lampenlebensdauer in Betriebsstunden (L80/B10)

LED Maschinenleuchte LED machine light



LEANLED II, 180 mm, opal white cover, cascadable

Item number: 111010-31
EAN: 4260556624211

Order number: 111010-31
Model: LEANLED II
Type: LED surface-mounted luminaire
Illuminant: SMD LED
Power consumption: ~4 W
Lamp luminous flux: 630 lm
Lamp luminous efficiency: 145 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)
Connected load: 24V DC ± 10%
Connection (connector): M12 A-type encoded
Degree of protection: IP54

Class of protection: III
Glare-free opal white

Beam angle (optics): 120°
Operating temperature: -10... +60 °C

Colour rendering (Ra): > 85
Lamps lifetime: > 60,000 h

Housing material: aluminium
Cover material: polycarbonate, soft

Height [B] x Width [C]: 31 mm x 26 mm
Length [A]: 180 mm

Weight (net): 180 g
Gross weight: 330 g

Risk group (DIN EN 62471): free group



Marking: CE, UKCA, ETL Listed (5003526)

Mounting accessories: 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope

Dimmable: via optional accessory

Made in: Germany

Feature: cascadable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.



Lamps lifetime in operation hours (L80/B10)