

# LED Maschinenleuchte



## LED machine light



## LEANLED II, 520 mm, opalweiße Abdeckung, kaskadierbar

**Artikel-Nr.:** 111010-34  
**EAN:** 4260556624242

<b>Bestell-Nr.:</b>	111010-34
<b>Modell:</b>	LEANLED II
<b>Bauform:</b>	LED Aufbauleuchte
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~13 W
<b>Lampenlichtstrom:</b>	1890 lm
<b>Lampenlichtausbeute:</b>	145 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC ± 10%
<b>Anschluss Leuchte:</b>	M12 A-kodiert
<b>Schutzart:</b>	IP54
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	opalweiß
<b>Abstrahlwinkel:</b>	120°
<b>Betriebstemperatur:</b>	-10... +60 °C
<b>Farbwiedergabe (Ra):</b>	> 85
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	Polycarbonat, matt
<b>Höhe [B] x Breite [C]:</b>	31 mm x 26 mm
<b>Länge [A]:</b>	520 mm
<b>Gewicht:</b>	350 g
<b>Bruttogewicht:</b>	600 g
<b>Risikogruppe (DIN EN 62471):</b>	freie Gruppe
<b>Kennzeichnung:</b>	CE, UKCA, ETL Listed (5003526)
<b>Befestigungszubehör:</b>	2 Paar Halterungen (drehbare oder planare Befestigung) im Lieferumfang
<b>Dimmbar:</b>	optional über Zubehör
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	kaskadierbar, mehrere Leuchten lassen sich bis max. 4A elektrisch verketteten



Lampenlebensdauer in Betriebsstunden (L80/B10)

LED Maschinenleuchte  
LED machine light





LEANLED II, 520 mm, opal white cover, cascadable

**Item number:** 111010-34  
**EAN:** 4260556624242

**Order number:** 111010-34  
**Model:** LEANLED II  
**Type:** LED surface-mounted luminaire  
**Illuminant:** SMD LED  
**Power consumption:** ~13 W  
**Lamp luminous flux:** 1890 lm  
**Lamp luminous efficiency:** 145 lm/W  
**Light distribution:** direct  
**Light colour:** daylight white (5200 - 5700K)  
**Connected load:** 24V DC ± 10%  
**Connection (connector):** M12 A-type encoded  
**Degree of protection:** IP54

**Class of protection:** III  
**Glare-free** opal white  
**Beam angle (optics):** 120°  
**Operating temperature:** -10... +60 °C  
**Colour rendering (Ra):** > 85  
**Lamps lifetime:** > 60,000 h  
**Housing material:** aluminium  
**Cover material:** Polycarbonate, soft  
**Height [B] x Width [C]:** 31 mm x 26 mm  
**Length [A]:** 520 mm  
**Weight (net):** 350 g  
**Gross weight:** 600 g

**Risk group (DIN EN 62471):** free group  
**Marking:** CE, UKCA, ETL Listed (5003526)  
**Mounting accessories:** 2 pairs mounting holders (holder for swivel or planar mounting) in delivery scope  
**Dimmable:** via optional accessory  
**Made in:** Germany  
**Feature:** cascadable, several luminaires can be interlinked electrically. The entire power consumption may not exceed 4A DC.



Lamps lifetime in operation hours (L80/B10)