

## LED Industrieleuchte



### LED industrial light



## INROLED\_25, 552 mm, 100°, 24V DC

**Artikel-Nr.:** 117110-01  
**EAN:** 4260556621562

<b>Bestell-Nr.:</b>	117110-01
<b>Modell:</b>	INROLED_25
<b>Bauform:</b>	LED Rohrleuchte
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~7,5 W
<b>Lampenlichtstrom:</b>	972 lm
<b>Lampenlichtausbeute:</b>	129 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC $\pm$ 10%
<b>Anschluss Leuchte:</b>	M12 Steckverbinder A-kodiert
<b>Schutzart:</b>	IP69K
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	opalweiß
<b>Abstrahlwinkel:</b>	100°
<b>Betriebstemperatur:</b>	-10... +50 °C
<b>Farbwiedergabe (Ra):</b>	> 80
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Abdeckung:</b>	Polycarbonat, splitterfrei
<b>Höhe [B] x Breite [C]:</b>	$\varnothing$ 25 mm
<b>Länge [A]:</b>	552 mm
<b>Gewicht:</b>	250 g
<b>Bruttogewicht:</b>	400 g
<b>Risikogruppe (DIN EN 62471):</b>	freie Gruppe
<b>Befestigungszubehör:</b>	Halterung inkl.
<b>Dimmbar:</b>	optional über Zubehör
<b>Kennzeichnung:</b>	CE, UKCA, ETL Listed (5003529)
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	Lebensmittelecht, beständig gegen Säure und Laugen (vorab Einzelfallprüfung)



Lampenlebensdauer in Betriebsstunden (L80/B10)



LED Industrieleuchte  
LED industrial light



**INROLED\_25, 552 mm, 100°, 24V DC**

**Item number:** 117110-01  
**EAN:** 4260556621562

<b>Order number:</b>	117110-01
<b>Model:</b>	INROLED_25
<b>Type:</b>	LED tube luminaire
<b>Illuminant:</b>	SMD LED
<b>Power consumption:</b>	~7,5 W
<b>Lamp luminous flux:</b>	972 lm
<b>Lamp luminous efficiency:</b>	129 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	daylight white (5200 - 5700K)
<b>Connected load:</b>	24V DC $\pm$ 10%
<b>Connection (connector):</b>	M12 connector A-type encoded
<b>Degree of protection:</b>	IP69K
<b>Class of protection:</b>	III
<b>Glare-free</b>	opal white
<b>Beam angle (optics):</b>	100°
<b>Operating temperature:</b>	-10... +50 °C
<b>Colour rendering (Ra):</b>	> 80
<b>Lamps lifetime:</b>	> 60,000 h
<b>Cover material:</b>	polycarbonate, shatterproof
<b>Height [B] x Width [C]:</b>	$\varnothing$ 25 mm
<b>Length [A]:</b>	552 mm
<b>Weight (net):</b>	250 g
<b>Gross weight:</b>	400 g
<b>Risk group (DIN EN 62471):</b>	free group
<b>Mounting accessories:</b>	incl. luminaire holders
<b>Dimmable:</b>	via optional accessory
<b>Marking:</b>	CE, UKCA, ETL Listed (5003529)
<b>Made in:</b>	Germany
<b>Feature:</b>	food-safe, resistant to acids and alkalis (case-by-case testing before)



Lamps lifetime in operation hours (L80/B10)