

LED Arbeitsplatzleuchte



LED workplace light



UNILED II Gelenkarm, dimmbar, 5200-5700K, Leuchtenbreite 298 mm

Artikelnr.: 120610-02
EAN: 4260556620268

Bestell-Nr.:	120610-02
Modell:	UNILED II Gelenkarm
Bauform:	LED Gelenkarmleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~14 W
Lampenlichtstrom:	1617 lm
Lampenlichtausbeute:	ca. 131 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC \pm 10%
Betriebsgerät:	Netzteil 110-240V AC inkl.
Anschluss Leuchte:	M12 Sensorstecker A-kodiert
Anschlusswert Netzteil:	100-240V AC
Anschluss Netzteil:	Netzstecker
Schutzart:	IP40
Schutzklasse:	III
Entblendung:	opalweiß
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +60 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium / Kunststoff
Material Abdeckung:	Kunststoff matt
Länge Kopf [A]:	298 mm
Länge Gelenkarme:	2x 400 mm
Gewicht:	1900 g
Bruttogewicht:	3550 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Befestigungszubehör:	Tischklemme inkl.
Dimmbar:	Dimmer mit Memory Funktion intern
Kennzeichnung:	CE, UKCA
Gefertigt in:	Deutschland
Besonderheit:	dimmbar, schmale Leuchtenbreite



Lampenlebensdauer in Betriebsstunden (L80/B10)



LED Arbeitsplatzleuchte
LED workplace light



UNILED II Gelenkarm (adjustable arm), dimmable, 5200-5700K, luminaire head width 298 mm

Item number: 120610-02
EAN: 4260556620268

Order number:	120610-02
Model:	UNILED II Gelenkarm (adjustable arm)
Type:	LED adjustable arm light
Illuminant:	SMD LED
Power consumption:	~14 W
Lamp luminous flux:	1617 lm
Lamp luminous efficiency:	ca. 131 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Power supply:	included external PSU 100-240V AC
Connection (connector):	M12 A-type encoded
Connected load PSU:	100-240V AC
Connection PSU:	power connection plug
Degree of protection:	IP40
Class of protection:	III
Glare-free	opal white
Beam angle (optics):	100°
Operating temperature:	-10... +60 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium / plastics
Cover material:	plastic soft
Head width [A]:	298 mm
Length adjustable arms:	2x 400 mm
Weight (net):	1900 g
Gross weight:	3550 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	included table clamp
Dimmable:	internal dimmer with memory function
Marking:	CE, UKCA
Made in:	Germany
Feature:	dimmable, short luminaire head



Lamps lifetime in operation hours (L80/B10)