


## LED Arbeitsplatzleuchte LED workplace light



### CENALED SPOT DC, Flexarm

**Artikelnr.:** 121012-01  
**EAN:** 4260556623719

|                                     |   |
|-------------------------------------|---|
| <b>Bestell-Nr.:</b>                 | 121012-01   |
| <b>Modell:</b>                      | CENALED SPOT  |
| <b>Bauform:</b>                     | LED Arbeitsplatzleuchte mit Schwanenhals                  |
| <b>Leuchtmittel:</b>                | High Power LED  |
| <b>Lampenleistung:</b>              | ~8,5 W  |
| <b>Lampenlichtstrom:</b>            | 1120 lm   |
| <b>Lampenlichtausbeute:</b>         | 134 lm/W  |
| <b>Lichtverteilung:</b>             | direkt  |
| <b>Lichtfarbe:</b>                  | Neutralweiß (5000K)                                       |
| <b>Anschlusswert Leuchte:</b>       | 24V DC ± 10%  |
| <b>Betriebsgerät:</b>               | -   |
| <b>Anschluss Leuchte:</b>           | 3 m Anschlussleitung, Ölflex, mit offenen Leitungsenden   |
| <b>Schutzart:</b>                   | IP67  |
| <b>Schutzklasse:</b>                | III   |
| <b>Abstrahlwinkel:</b>              | 30°   |
| <b>Betriebstemperatur:</b>          | -10... +50 °C   |
| <b>Farbwiedergabe (Ra):</b>         | > 80  |
| <b>Lampenlebensdauer:</b>           | > 60.000 h  |
| <b>Material Gehäuse:</b>            | Aluminium (pulverlackiert)                                |
| <b>Material Abdeckung:</b>          | Sicherheitsglas, sprungsicher                             |
| <b>Länge Flexarm [A]:</b>           | 500 mm  |
| <b>Sockelhöhe (B):</b>              | 59 mm   |
| <b>Befestigung:</b>                 | Anschraubsockel   |
| <b>Gewicht:</b>                     | 800 g   |
| <b>Bruttogewicht:</b>               | 1400 g  |
| <b>Risikogruppe (DIN EN 62471):</b> | freie Gruppe  |
| <b>Befestigungszubehör:</b>         | Magnethalterung optional                                  |
| <b>Dimmbar:</b>                     | ja, über Taster am Leuchtenkopf, Ein/Aus und Dimmen       |
| <b>Kennzeichnung:</b>               | CE, UKCA, ETL Listed (5003529) (5003529)                  |
| <b>Gefertigt in:</b>                | Deutschland   |
| <b>Besonderheit:</b>                | Universell einsetzbare Arbeitsleuchte mit hoher Schutzart |



Lampenlebensdauer in Betriebsstunden (L80/B10)


## LED Arbeitsplatzleuchte LED workplace light



### CENALED SPOT DC, Flexarm

**Item number:** 121012-01  
**EAN:** 4260556623719

|                                   |  |
|-----------------------------------|--|
| <b>Order number:</b>              | 121012-01  |
| <b>Model:</b>                     | CENALED SPOT   |
| <b>Type:</b>                      | LED workplace light with gooseneck                             |
| <b>Illuminant:</b>                | High Power LED   |
| <b>Power consumption:</b>         | ~8,5 W   |
| <b>Lamp luminous flux:</b>        | 1120 lm  |
| <b>Lamp luminous efficiency:</b>  | 134 lm/W   |
| <b>Light distribution:</b>        | direct   |
| <b>Light colour:</b>              | neutral white (5000K)  |
| <b>Connected load:</b>            | 24V DC $\pm$ 10%   |
| <b>Power supply:</b>              | -  |
| <b>Connection (connector):</b>    | connection cable 3m, flexible, two open cable ends             |
| <b>Degree of protection:</b>      | IP67   |
| <b>Class of protection:</b>       | III  |
| <b>Beam angle (optics):</b>       | 30°  |
| <b>Operating temperature:</b>     | -10... +50 °C  |
| <b>Colour rendering (Ra):</b>     | > 80   |
| <b>Lamps lifetime:</b>            | > 60,000 h   |
| <b>Housing material:</b>          | aluminium (powder finished)                                    |
| <b>Cover material:</b>            | safety glass, shatterproof                                     |
| <b>Length Flexarm [A]:</b>        | 500 mm   |
| <b>Base height (B):</b>           | 59 mm  |
| <b>Mounting:</b>                  | screw-on base  |
| <b>Weight (net):</b>              | 800 g  |
| <b>Gross weight:</b>              | 1400 g   |
| <b>Risk group (DIN EN 62471):</b> | free group   |
| <b>Mounting accessories:</b>      | magnet holder plate optional                                   |
| <b>Dimmable:</b>                  | yes, via push button at the luminaire head, ON/OFF and dimming |
| <b>Marking:</b>                   | CE, UKCA, ETL Listed (5003529)                                 |
| <b>Made in:</b>                   | Germany  |
| <b>Feature:</b>                   | universal workplace light with high protection degree          |



Lamps lifetime in operation hours (L80/B10)