


## LED Maschinenleuchte LED machine light



### CENALED SPOT DC, Gelenkkopf

**Artikel-Nr.:** 121012-03  
**EAN:** 4260556623733

<b>Bestell-Nr.:</b>	121012-03
<b>Modell:</b>	CENALED SPOT
<b>Bauform:</b>	LED Gelenkkopfleuchte
<b>Leuchtmittel:</b>	High Power LED
<b>Lampenleistung:</b>	~8,5 W
<b>Lampenlichtstrom:</b>	1120 lm
<b>Lampenlichtausbeute:</b>	134 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Neutralweiß (5000K)
<b>Anschlusswert Leuchte:</b>	24V DC ± 10%
<b>Betriebsgerät:</b>	-
<b>Anschluss Leuchte:</b>	Anschlussleitung, Ölflex, mit offenen Leitungsenden
<b>Schutzart:</b>	IP67
<b>Schutzklasse:</b>	III
<b>Abstrahlwinkel:</b>	30°
<b>Betriebstemperatur:</b>	-10... +50 °C
<b>Farbwiedergabe (Ra):</b>	> 80
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium (pulverlackiert)
<b>Material Abdeckung:</b>	ESG 3,8 mm, sprungsicher
<b>Sockelhöhe (B):</b>	59 mm
<b>Gewicht:</b>	400 g
<b>Bruttogewicht:</b>	550 g
<b>Risikogruppe (DIN EN 62471):</b>	freie Gruppe
<b>Befestigungszubehör:</b>	Magnethalterung optional
<b>Dimmbar:</b>	ja, über Taster am Leuchtenkopf, Ein/Aus und Dimmen
<b>Kennzeichnung:</b>	CE, UKCA, ETL Listed (5003526)
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	Universell einsetzbare LED Leuchte mit hoher Schutzart



Lampenlebensdauer in Betriebstunden (L80/B10)


LED Maschinenleuchte  
LED machine light



**CENALED SPOT DC, Gelenkkopf**  
Joint head luminaire

**Item number:** 121012-03  
**EAN:** 4260556623733

<b>Order number:</b>	121012-03
<b>Model:</b>	CENALED SPOT
<b>Type:</b>	LED joint head luminaire
<b>Illuminant:</b>	High Power LED
<b>Power consumption:</b>	~8,5 W
<b>Lamp luminous flux:</b>	1120 lm
<b>Lamp luminous efficiency:</b>	134 lm/W
<b>Light distribution:</b>	direct
<b>Light colour:</b>	neutral white (5000K)
<b>Connected load:</b>	24V DC $\pm$ 10%
<b>Power supply:</b>	-
<b>Connection (connector):</b>	connection cable 3 m, oelflex, with open ends
<b>Degree of protection:</b>	IP67
<b>Class of protection:</b>	III
<b>Beam angle (optics):</b>	30°
<b>Operating temperature:</b>	-10... +50 °C
<b>Colour rendering (Ra):</b>	> 80
<b>Lamps lifetime:</b>	> 60,000 h
<b>Housing material:</b>	aluminium (powder-finished)
<b>Cover material:</b>	ESG 3,8 mm, shatterproof
<b>Base height (B):</b>	59 mm
<b>Weight (net):</b>	400 g
<b>Gross weight:</b>	550 g
<b>Risk group (DIN EN 62471):</b>	free group
<b>Mounting accessories:</b>	magnetic holder optional
<b>Dimmable:</b>	yes, via push button at the luminaire head , ON/OFF and dimming
<b>Marking:</b>	CE, UKCA, ETL Listed (5003526)
<b>Made in:</b>	Germany
<b>Feature:</b>	handy LED luminaire with high degree of protection



Lamps lifetime in operation hours (L80/B10)