

# LED Arbeitsplatzleuchte


## LED workplace light





### PROFILED DC, 500 mm, mit Dimmer, Abdeckung Mikroprismen, 24V DC

**Artikel-Nr.:** 150314-02  
**EAN:** 4260556623818

<b>Bestell-Nr.:</b>	150314-02
<b>Modell:</b>	PROFILED
<b>Bauform:</b>	Profilleuchte mit T-Nut rückseitig
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~11 W
<b>Lampenlichtstrom:</b>	1575 lm
<b>Lampenlichtausbeute:</b>	145 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC ± 10%
<b>Anschluss Leuchte:</b>	M12 Steckverbinder A-kodiert
<b>Schutzart:</b>	IP40
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	Mikroprismen
<b>Abstrahlwinkel:</b>	100°
<b>Betriebstemperatur:</b>	-10... +60 °C
<b>Farbwiedergabe (Ra):</b>	> 85
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	Kunststoff
<b>Höhe [B] x Breite [C]:</b>	65 mm x 45 mm
<b>Länge [A]:</b>	500 mm
<b>Gewicht:</b>	850 g
<b>Bruttogewicht:</b>	1300 g
<b>Risikogruppe (DIN EN 62471):</b>	freie Gruppe
<b>Befestigungszubehör:</b>	optional
<b>Dimmbar:</b>	Dimmer intern
<b>Kennzeichnung:</b>	CE, UKCA
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	mit Dimmer, universell als Werkbankleuchte, Systemleuchte oder Industrieleuchte



Abstand d=100 cm

 $E_{\text{mitte}} = 399 \text{ lux}$  $E_{\text{rand}} = 575 \text{ lux}$  $E_{\text{min}} = 209 \text{ lux}$ 

Lampenlebensdauer in Betriebsstunden (L80/B10)

## LED Arbeitsplatzleuchte LED workplace light



### PROFILED DC, 500 mm, with dimmer micro prisms cover, 24V DC

**Item number:** 150314-02  
**EAN:** 4260556623818

**Order number:** 150314-02  
**Model:** PROFILED  
**Type:** profiled light with t-slot backsided  
**Illuminant:** SMD LED  
**Power consumption:** ~11 W  
**Lamp luminous flux:** 1575 lm  
**Lamp luminous efficiency:** 145 lm/W  
**Light distribution:** direct  
**Light colour:** daylight white (5200 - 5700K)  
**Connected load:** 24V DC  $\pm$  10%  
**Connection (connector):** M12 A-type encoded  
**Degree of protection:** IP40

**Class of protection:** III  
**Glare-free** micro prisms

**Beam angle (optics):** 100°  
**Operating temperature:** -10... +60 °C

**Colour rendering (Ra):** > 85  
**Lamps lifetime:** > 60,000 h


**Housing material:** aluminium  
**Cover material:** plastics  
**Height [B] x Width [C]:** 65 mm x 45 mm

**Length [A]:** 500 mm  
**Weight (net):** 850 g  
**Gross weight:** 1300 g



**Risk group (DIN EN 62471):** free group  
**Mounting accessories:** optional

**Dimmable:** internal dimmer control  
**Marking:** CE, UKCA  
**Made in:** Germany

**Feature:** with dimming control, universally accepted as workbench lighting, system light or industrial light



Abstand d=100 cm  
 $E_{\text{mittel}} = 399 \text{ lux}$   
 $E_{\text{max}} = 575 \text{ lux}$   
 $E_{\text{min}} = 209 \text{ lux}$



Lamps lifetime in operation hours (L80/B10)