

LED Arbeitsplatzleuchte




LED workplace light



PROFILED AC, 500 mm, Abdeckung Mikroprismen

Artikel-Nr.: 150314-07
EAN: 4260556626413

Bestell-Nr.:	150314-07
Modell:	PROFILED
Bauform:	Profilleuchte mit T-Nut rückseitig
Leuchtmittel:	SMD LED
Lampenleistung:	~14 W
Lampenlichtstrom:	1575 lm
Lampenlichtausbeute:	145 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	90-305V AC ± 10%, 50-60 Hz
Betriebsgerät:	integriert
Anschluss Leuchte:	GST18
Schutzart:	IP40
Schutzklasse:	I
Entblendung:	Mikroprismen
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +45 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Kunststoff
Höhe [B] x Breite [C]:	65 mm x 45 mm
Länge [A]:	500 mm
Gewicht:	1300 g
Bruttogewicht:	1750 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Befestigungszubehör:	optional
Kennzeichnung:	CE, UKCA
Gefertigt in:	Deutschland
Besonderheit:	Universalleuchte



Lampenlebensdauer in Betriebsstunden (L80/B10)

LED Arbeitsplatzleuchte
LED workplace light






PROFILED AC, 500 mm, micro prisms cover

Item number: 150314-07
EAN: 4260556626413

Order number: 150314-07
Model: PROFILED
Type: profiled light with t-slot backsided
Illuminant: SMD LED
Power consumption: ~14 W
Lamp luminous flux: 1575 lm
Lamp luminous efficiency: 145 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)
Connected load: 90-305V AC \pm 10%, 50-60 Hz
Power supply: inbuilt
Connection (connector): GST18

Degree of protection: IP40
Class of protection: I
Glare-free micro prisms
Beam angle (optics): 100°
Operating temperature: -10... +45 °C
Colour rendering (Ra): > 85
Lamps lifetime: > 60,000 h
Housing material: aluminium
Cover material: plastics
Height [B] x Width [C]: 65 mm x 45 mm
Length [A]: 500 mm
Weight (net): 1300 g
Gross weight: 1750 g
Risk group (DIN EN 62471): free group
Mounting accessories: optional
Marking: CE, UKCA
Made in: Germany
Feature: universal light



Lamps lifetime in operation hours (L80/B10)