

LED Arbeitsplatzleuchte

LED workplace light



PPROFILED DC, 900 mm, mit Dimmer, Abdeckung Mikroprismen, 24V DC

Artikel-Nr.: 150614-02
EAN: 4260556623825

Bestell-Nr.: 150614-02
Modell: PROFILED
Bauform: Profilleuchte mit T-Nut rückseitig
Leuchtmittel: SMD LED
Lampenleistung: ~21 W
Lampenlichtstrom: 3150 lm
Lampenlichtausbeute: 145 lm/W
Lichtverteilung: direkt
Lichtfarbe: Tageslichtweiß (5200 - 5700K)

Anschlusswert Leuchte: 24V DC \pm 10%
Anschluss Leuchte: M12 Steckverbinder A-kodiert
Schutzart: IP40

Schutzklasse: III
Entblendung: Mikroprismen
Abstrahlwinkel: 100°

Betriebstemperatur: -10... +60 °C
Farbwiedergabe (Ra): > 85
Lampenlebensdauer: > 60.000 h

Material Gehäuse: Aluminium
Material Abdeckung: Kunststoff
Höhe [B] x Breite [C]: 65 mm x 45 mm
Länge [A]: 900 mm


Gewicht: 1650 g
Bruttogewicht: 2200 g

Risikogruppe (DIN EN 62471): freie Gruppe

Befestigungszubehör: optional
Dimmbar: Dimmer intern



Kennzeichnung: CE, UKCA
Gefertigt in: Deutschland

Besonderheit: mit Dimmer, universell als Werkbankleuchte, Systemleuchte oder Industrieleuchte



Abstand d=100 cm

$E_{\text{mittel}} = 708 \text{ lux}$
 $E_{\text{max}} = 980 \text{ lux}$
 $E_{\text{min}} = 392 \text{ lux}$



Lampenlebensdauer in Betriebstunden (L80/B10)

LED Arbeitsplatzleuchte LED workplace light



PPROFILED DC, 900 mm, with dimmer micro prisms cover, 24V DC

Item number: 150614-02
EAN: 4260556623825

Order number: 150614-02
Model: PROFILED
Type: profiled light with t-slot backsided
Illuminant: SMD LED
Power consumption: ~21 W
Lamp luminous flux: 3150 lm
Lamp luminous efficiency: 145 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)
Connected load: 24V DC ± 10%
Connection (connector): M12 A-type encoded

Degree of protection: IP40
Class of protection: III
Glare-free micro prisms

Beam angle (optics): 100°
Operating temperature: -10... +60 °C
Colour rendering (Ra): > 85

Lamps lifetime: > 60,000 h
Housing material: aluminium




Cover material: plastics
Height [B] x Width [C]: 65 mm x 45 mm

Length [A]: 900 mm
Weight (net): 1650 g
Gross weight: 2200 g

Risk group (DIN EN 62471): free group
Mounting accessories: optional

Dimmable: internal dimmer control
Marking: CE, UKCA

Made in: Germany
Feature: with dimming control, universally accepted as workbench lighting, system light or industrial light



Lamps lifetime in operation hours (L80/B10)