

LED Arbeitsplatzleuchte




LED workplace light



PROFILED AC, 900 mm, mit Dimmer, Abdeckung Mikroprismen, 90-305V AC

Artikel-Nr.: 150614-04
EAN: 4260556623900

Bestell-Nr.:	150614-04
Modell:	PROFILED
Bauform:	Profilleuchte mit T-Nut rückseitig
Leuchtmittel:	SMD LED
Lampenleistung:	~24 W
Lampenlichtstrom:	3150 lm
Lampenlichtausbeute:	145 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	90-305V AC ± 10%, 50-60 Hz
Betriebsgerät:	integriert
Anschluss Leuchte:	Anschlussleitung mit Netzstecker
Schutzart:	IP40
Schutzklasse:	I
Entblendung:	Mikroprismen
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +45 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Kunststoff
Höhe [B] x Breite [C]:	65 mm x 45 mm
Länge [A]:	900 mm
Gewicht:	2200 g
Bruttogewicht:	2750 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Befestigungszubehör:	optional
Dimmbar:	Dimmer intern
Kennzeichnung:	CE, UKCA
Gefertigt in:	Deutschland
Besonderheit:	Universalleuchte mit Dimmer



Lampenlebensdauer in Betriebsstunden (L80/B10)

LED Arbeitsplatzleuchte
LED workplace light



**PROFILED AC, 900 mm, with dimmer
micro prisms cover, 90-305V AC**

Item number: 150614-04
EAN: 4260556623900

Order number: 150614-04
Model: PROFILED
Type: profiled light with t-slot backsided
Illuminant: SMD LED
Power consumption: ~24 W
Lamp luminous flux: 3150 lm
Lamp luminous efficiency: 145 lm/W
Light distribution: direct
Light colour: daylight white (5200 - 5700K)
Connected load: 90-305V AC ± 10%, 50-60 Hz
Power supply: inbuilt




Connection (connector): connection cable with power plug

Degree of protection: IP40
Class of protection: I
Glare-free micro prisms
Beam angle (optics): 100°
Operating temperature: -10... +45 °C

Colour rendering (Ra): > 85
Lamps lifetime: > 60,000 h

Housing material: aluminium
Cover material: plastics
Height [B] x Width [C]: 65 mm x 45 mm
Length [A]: 900 mm

Weight (net): 2200 g
Gross weight: 2750 g
Risk group (DIN EN 62471): free group
Mounting accessories: optional
Dimmable: internal dimmer control
Marking: CE, UKCA
Made in: Germany
Feature: universal light , dimmable



Lamps lifetime in operation hours (L80/B10)