

LED Arbeitsplatzleuchte

LED workplace light



PROFILED DC, 1000 mm, mit Dimmer, Abdeckung Mikroprismen, 24V DC

Artikel-Nr.: 150714-02
EAN: 4260556623832

Bestell-Nr.: 150714-02
Modell: PROFILED
Bauform: Profilleuchte mit T-Nut rückseitig
Leuchtmittel: SMD LED
Lampenleistung: ~23 W
Lampenlichtstrom: 3565 lm
Lampenlichtausbeute: 145 lm/W
Lichtverteilung: direkt
Lichtfarbe: Tageslichtweiß (5200 - 5700K)

Anschlusswert Leuchte: 24V DC \pm 10 %

Anschluss Leuchte: M12 Steckverbinder A-kodiert

Schutzart: IP40

Schutzklasse: III

Entblendung: Mikroprismen

Abstrahlwinkel: 100°

Betriebstemperatur: -10... +60 °C

Farbwiedergabe (Ra): > 85

Lampenlebensdauer: > 60.000 h

Material Gehäuse: Aluminium

Material Abdeckung: Kunststoff

Höhe [B] x Breite [C]: 65 mm x 45 mm

Länge [A]: 1000 mm

Gewicht: 1875 g

Bruttogewicht: 2520 g

Risikogruppe (DIN EN 62471): freie Gruppe


Befestigungszubehör: optional

Dimmbar: Dimmer intern

Kennzeichnung: CE, UKCA

Gefertigt in: Deutschland

Besonderheit: mit Dimmer, universell als Werkbankleuchte, Systemleuchte oder Industrieleuchte





Abstand d=100 cm

$E_{\text{mittel}} = 761 \text{ lux}$

$E_{\text{max}} = 1041 \text{ lux}$

$E_{\text{min}} = 428 \text{ lux}$



Lampenlebensdauer in Betriebstunden (L80/B10)




LED Arbeitsplatzleuchte LED workplace light



PROFILED DC, 1000 mm, with dimmer micro prisms cover, 24V DC

Item number: 150714-02
EAN: 4260556623832

Order number:	150714-02
Model:	PROFILED
Type:	pofiled light with t-slot backsided
Illuminant:	SMD LED
Power consumption:	~23 W
Lamp luminous flux:	3565 lm
Lamp luminous efficiency:	145 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	24V DC \pm 10%
Connection (connector):	M12 A-type encoded
Degree of protection:	IP40
Class of protection:	III
Glare-free	micro prisms
Beam angle (optics):	100°
Operating temperature:	-10... +60 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm
Length [A]:	1000 mm
Weight (net):	1875 g
Gross weight:	2520 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	optional
Dimmable:	internal dimmer control
Marking:	CE, UKCA
Made in:	Germany
Feature:	with dimming control, universally accepted as workbench lighting, system light or industrial light



Lamps lifetime in operation hours (L80/B10)