

# LED Arbeitsplatzleuchte




## LED workplace light



### PROFILED AC, 1000 mm, Abdeckung Mikroprismen, 90-305V AC

**Artikel-Nr.:** 150714-03  
**EAN:** 4260556623870

<b>Bestell-Nr.:</b>	150714-03
<b>Modell:</b>	PROFILED
<b>Bauform:</b>	Profilleuchte mit T-Nut rückseitig
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~27 W
<b>Lampenlichtstrom:</b>	3465 lm
<b>Lampenlichtausbeute:</b>	145 lm/W
<b>Lichtverteilung:</b>	direkt
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	90-305V AC ± 10%, 50-60 Hz
<b>Betriebsgerät:</b>	integriert
<b>Anschluss Leuchte:</b>	Anschlussleitung mit Netzstecker
<b>Schutzart:</b>	IP40
<b>Schutzklasse:</b>	I
<b>Entblendung:</b>	Mikroprismen
<b>Abstrahlwinkel:</b>	100°
<b>Betriebstemperatur:</b>	-10... +45 °C
<b>Farbwiedergabe (Ra):</b>	> 85
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	Kunststoff
<b>Höhe [B] x Breite [C]:</b>	65 mm x 45 mm
<b>Länge [A]:</b>	1000 mm
<b>Gewicht:</b>	2400 g
<b>Bruttogewicht:</b>	3050 g
<b>Risikogruppe (DIN EN 62471):</b>	freie Gruppe
<b>Befestigungszubehör:</b>	optional
<b>Kennzeichnung:</b>	CE, UKCA
<b>Gefertigt in:</b>	Deutschland
<b>Besonderheit:</b>	Universalleuchte



Lampenlebensdauer in Betriebstunden (L80/B10)




LED Arbeitsplatzleuchte  
LED workplace light



**PROFILED AC, 1000 mm,  
micro prisms cover, 90-305V AC**

**Item number:** 150714-03  
**EAN:** 4260556623870

**Order number:** 150714-03  
**Model:** PROFILED  
**Type:** profiled light with t-slot backsided  
**Illuminant:** SMD LED  
**Power consumption:** ~27 W  
**Lamp luminous flux:** 3465 lm  
**Lamp luminous efficiency:** 145 lm/W  
**Light distribution:** direct  
**Light colour:** daylight white (5200 - 5700K)  
**Connected load:** 90-305V AC ± 10%, 50-60 Hz  
**Power supply:** inbuilt  
**Connection (connector):** connection cable with power plug  
**Degree of protection:** IP40  
**Class of protection:** I  
**Glare-free** micro prisms  
**Beam angle (optics):** 100°  
**Operating temperature:** -10... +45 °C  
**Colour rendering (Ra):** > 85  
**Lamps lifetime:** > 60,000 h  
**Housing material:** aluminium  
**Cover material:** plastics  
**Height [B] x Width [C]:** 65 mm x 45 mm  
**Length [A]:** 1000 mm  
**Weight (net):** 2400 g  
**Gross weight:** 3050 g  
**Risk group (DIN EN 62471):** free group  
**Mounting accessories:** optional  
**Marking:** CE, UKCA  
**Made in:** Germany  
**Feature:** universal light



Lamps lifetime in operation hours (L80/B10)