

LED Arbeitsplatzleuchte


LED workplace light



PROFILED AC Zugpendel, Abdeckung Mikroprismen, 90-305V AC



Artikel-Nr.: 150714-05
EAN: 4260556625775

Bestell-Nr.:	150714-05
Modell:	PROFILED
Bauform:	Profilleuchte mit Zugpendelabhängung
Geräteleistung:	~27 W
Leuchtmittel:	SMD LED
Lampenleistung:	~23 W
Lampenlichtstrom:	3465 lm
Lampenlichtausbeute:	145 lm/W
Lichtverteilung:	direkt
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	90-305V AC ± 10%, 50-60 Hz
Betriebsgerät:	integriert
Anschluss Leuchte:	1 Paar Zugpendel, Deckenübergabepunkt, offene Kabelenden
Schutzart:	IP40
Schutzklasse:	I
Entblendung:	Mikroprismen
Abstrahlwinkel:	100°
Betriebstemperatur:	-10... +45 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Kunststoff
Höhe [B] x Breite [C]:	65 mm x 45 mm
Länge [A]:	1000 mm
Zugpendel Auszugsbereich:	~900 mm - 1800 mm
Gewicht:	3000 g
Bruttogewicht:	3650 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Befestigungszubehör:	optional
Kennzeichnung:	CE, UKCA
Gefertigt in:	Deutschland



Abstand d=100 cm

$E_{\text{mittel}} = 761 \text{ lux}$
 $E_{\text{max}} = 1041 \text{ lux}$
 $E_{\text{min}} = 428 \text{ lux}$



Lampenlebensdauer in Betriebstunden (L80/B10)




LED Arbeitsplatzleuchte
LED workplace light



**PROFILED AC Zugpendel,
micro prisms cover, 90-305V AC**

Item number: 150714-05
EAN: 4260556625775

Order number:	150714-05
Model:	PROFILED
Type:	pofiled light with adjustable pull pendants
Complete consumption:	~27 W
Illuminant:	SMD LED
Lamp consumption:	~23 W
Lamp luminous flux:	3465 lm
Lamp luminous efficiency:	145 lm/W
Light distribution:	direct
Light colour:	daylight white (5200 - 5700K)
Connected load:	90-305V AC ± 10%, 50-60 Hz
Power supply:	inbuilt
Connection (connector):	1 pair of adjustable pull pendants, ceiling transferpoint via open cable ends
Degree of protection:	IP40
Class of protection:	I
Glare-free	micro prisms
Beam angle (optics):	100°
Operating temperature:	-10... +45 °C
Colour rendering (Ra):	> 85
Lamps lifetime:	> 60,000 h
Housing material:	aluminium
Cover material:	plastics
Height [B] x Width [C]:	65 mm x 45 mm
Length [A]:	1000 mm
adjustable pull pendants	~900 mm - 1800 mm
Weight (net):	3000 g
Gross weight:	3650 g
Risk group (DIN EN 62471):	free group
Mounting accessories:	optional
Marking:	CE, UKCA
Made in:	Germany



Lamps lifetime in operation hours (L80/B10)