

LED Maschinenleuchte


LED machine light



TUBELED_40 II Integrated, 395 mm x 74 mm x 3 mm

Artikel-Nr.: 151110-01
EAN: 4260556623955

Bestell-Nr.:	151110-01
Modell:	TUBELED_40 II Integrated
Bauform:	LED Einbauleuchte
Leuchtmittel:	SMD LED
Lampenleistung:	~16 W
Lampenlichtstrom:	2139 lm
Lampenlichtausbeute:	131 lm/W
Lichtverteilung:	Light Forming Technology
Lichtfarbe:	Tageslichtweiß (5200 - 5700K)
Anschlusswert Leuchte:	24V DC \pm 10%
Anschluss Leuchte:	M12 A-kodiert
Schutzart:	IP67/IP69K
Schutzklasse:	III
Entblendung:	Diffusor ESG
Abstrahlwinkel:	100°
Betriebstemperatur:	-30... +60 °C
Farbwiedergabe (Ra):	> 85
Lampenlebensdauer:	> 60.000 h
Material Gehäuse:	Aluminium
Material Abdeckung:	Sicherheitsglas, 4 mm
Höhe [B] x Breite [C]:	32 mm x 74 mm, Blende 3 mm aufbauend
Länge [A]:	395 mm
Gewicht:	700 g
Bruttogewicht:	950 g
Risikogruppe (DIN EN 62471):	freie Gruppe
Kennzeichnung:	CE, UKCA, ETL Listed (5003526)
Dimmbar:	optional über Zubehör
Gefertigt in:	Deutschland



TUBELED_40 II Integrated 151110-01
 TUBELED_40 II Integrated RGB-W 151190-01

Lampenlebensdauer in Betriebsstunden (L80/B10)

LED Maschinenleuchte
LED machine light



Recessed luminaire TUBELED_40 II Integrated,
395 mm x 74 mm x 3 mm

Item number: 151110-01
EAN: 4260556623955

Order number: 151110-01
Model: TUBELED_40 II Integrated
Type: LED recessed luminaire
Illuminant: SMD LED
Power consumption: ~16 W
Lamp luminous flux: 2139 lm
Lamp luminous efficiency: 131 lm/W
Light distribution: Light Forming Technology
Light colour: daylight white (5200 - 5700K)
Connected load: 24V DC \pm 10%
Connection (connector): M12 A-type encoded
Degree of protection: IP67/IP69K
Class of protection: III
Glare-free diffused safety glass
Beam angle (optics): 100°
Operating temperature: -30... +60 °C
Colour rendering (Ra): > 85
Lamps lifetime: > 60,000 h
Housing material: aluminium
Cover material: Safety glass, 4 mm
Height [B] x Width [C]: 32 mm x 74 mm, Cover plate 3 mm externally
Length [A]: 395 mm
Weight (net): 700 g
Gross weight: 950 g
Risk group (DIN EN 62471): free group
Marking: CE, UKCA, ETL Listed (5003526)
Dimmable: via optional accessory
Made in: Germany



TUBELED_40 II Integrated 151110-01
TUBELED_40 II Integrated RGB-W 151190-01

Lamps lifetime in operation hours (L80/B10)