

## LED Maschinenleuchte


### LED machine light



## TUBELED\_40 II Integrated, 745 mm x 74 mm x 3 mm

**Artikel-Nr.:** 151310-01  
**EAN:** 4260556623979

<b>Bestell-Nr.:</b>	151310-01
<b>Modell:</b>	TUBELED_40 II Integrated
<b>Bauform:</b>	LED Einbauleuchte
<b>Leuchtmittel:</b>	SMD LED
<b>Lampenleistung:</b>	~24 W
<b>Lampenlichtstrom:</b>	3217 lm
<b>Lampenlichtausbeute:</b>	131 lm/W
<b>Lichtverteilung:</b>	Light Forming Technology
<b>Lichtfarbe:</b>	Tageslichtweiß (5200 - 5700K)
<b>Anschlusswert Leuchte:</b>	24V DC ± 10%
<b>Anschluss Leuchte:</b>	M12 A-kodiert
<b>Schutzart:</b>	IP67/IP69K
<b>Schutzklasse:</b>	III
<b>Entblendung:</b>	Diffusor ESG
<b>Abstrahlwinkel:</b>	100°
<b>Betriebstemperatur:</b>	-30... +60 °C
<b>Farbwiedergabe (Ra):</b>	> 85
<b>Lampenlebensdauer:</b>	> 60.000 h
<b>Material Gehäuse:</b>	Aluminium
<b>Material Abdeckung:</b>	Sicherheitsglas, 4 mm
<b>Höhe [B] x Breite [C]:</b>	32 mm x 74 mm, Blende 3 mm aufbauend
<b>Länge [A]:</b>	745 mm
<b>Gewicht:</b>	1100 g
<b>Bruttogewicht:</b>	1350 g
<b>Risikogruppe (DIN EN 62471):</b>	freie Gruppe
<b>Kennzeichnung:</b>	CE, UKCA, ETL Listed (5003526)
<b>Dimmbar:</b>	optional über Zubehör
<b>Gefertigt in:</b>	Deutschland



TUBELED\_40 II Integrated 151310-01  
 TUBELED\_40 II Integrated RGB-W 151390-01

Lampenlebensdauer in Betriebsstunden (L80/B10)


LED Maschinenleuchte  
LED machine light



Recessed luminaire TUBELED\_40 II Integrated,  
745 mm x 74 mm x 3 mm

**Item number:** 151310-01  
**EAN:** 4260556623979

**Order number:** 151310-01  
**Model:** TUBELED\_40 II Integrated  
**Type:** LED recessed luminaire  
**Illuminant:** SMD LED  
**Power consumption:** ~24 W  
**Lamp luminous flux:** 3217 lm  
**Lamp luminous efficiency:** 131 lm/W  
**Light distribution:** Light Forming Technology  
**Light colour:** daylight white (5200 - 5700K)  
**Connected load:** 24V DC  $\pm$  10%  
**Connection (connector):** M12 A-type encoded  
**Degree of protection:** IP67/IP69K  
**Class of protection:** III  
**Glare-free** diffused safety glass  
**Beam angle (optics):** 100°  
**Operating temperature:** -30... +60 °C  
**Colour rendering (Ra):** > 85  
**Lamps lifetime:** > 60,000 h  
**Housing material:** aluminium  
**Cover material:** Safety glass, 4 mm  
**Height [B] x Width [C]:** 32 mm x 74 mm, Cover plate 3 mm externally  
**Length [A]:** 745 mm  
**Weight (net):** 1100 g  
**Gross weight:** 1350 g  
**Risk group (DIN EN 62471):** free group  
**Marking:** CE, UKCA, ETL Listed (5003526)  
**Dimmable:** via optional accessory  
**Made in:** Germany



TUBELED\_40 II Integrated 151310-01  
TUBELED\_40 II Integrated RGB-W 151390-01

Lamps lifetime in operation hours (L80/B10)